

ZODZ.E307428 - Positioning Devices

Positioning Devices

SUZHOU HUIHUA ELECTRONICS TECH CO LTD

No.29 East Jinzhi Road, New District
Suzhou, Jiangsu 215151 China

E307428

Nonmetallic Cable Ties Investigated to ANSI/UL 62275

Cat. No.	Type Dsg.	Bundle Dia. mm		Loop Tensile Str. N	Operating Temp. °C		Min. Install. Temp. °C	Resistant to UV Light	Plenum Rating	Also Classified to [^] IEC 62275 and EN 62275
		Min	Max		Min	Max				
GT-100M	21	3	22	80	-40	85	-10	-	-	-
GT-100MB UV	21	3	22	80	-40	85	-10	Y	-	-
GT-1168HDL	21	10	340	800	-40	85	-10	-	-	-
GT-1168HDLB UV	21	10	340	800	-40	85	-10	Y	-	-
GT-120M	21	3	25	80	-40	85	-10	-	-	-
GT-120MB UV	21	3	25	80	-40	85	-10	Y	-	-
GT-120ST	21	3	24	220	-40	85	-10	-	-	-
GT-120STB UV	21	3	24	220	-40	85	-10	Y	-	-
GT-150HD	21	6	33	530	-40	85	-10	-	-	-
GT-150HDB UV	21	6	33	530	-40	85	-10	Y	-	-
GT-150I	21	3	35	180	-40	85	0	-	-	-
GT-150IB UV	21	3	35	180	-40	85	0	Y	-	-
GT-150M	21	3	35	80	-40	85	-10	-	-	-
GT-150MB UV	21	3	35	80	-40	85	-10	Y	-	-
GT-150ST	21	3	35	220	-40	85	-10	-	-	-
GT-150STB UV	21	3	35	220	-40	85	-10	Y	-	-
GT-160M	21	3	40	80	-40	85	-10	-	-	-
GT-160MB UV	21	3	40	80	-40	85	-10	Y	-	-
GT-190ST	21	3	46	220	-40	85	-10	-	-	-

GT-190STB UV	21	3	46	220	-40	85	-10	Y	-	-
GT-200HD	21	6	50	530	-40	85	-10	-	-	-
GT-200HDB UV	21	6	50	530	-40	85	-10	Y	-	-
GT-200I	21	3	50	180	-40	85	-10	-	-	-
GT-200IB UV	21	3	50	180	-40	85	-10	Y	-	-
GT-200M	21	3	50	80	-40	85	-10	-	-	-
GT-200MB UV	21	3	50	80	-40	85	-10	Y	-	-
GT-200ST	21	3	50	220	-40	85	-10	-	-	-
GT-200STB UV	21	3	50	220	-40	85	-10	Y	-	-
GT-250HD	21	6	65	530	-40	85	-10	-	-	-
GT-250HDB UV	21	6	65	530	-40	85	-10	Y	-	-
GT-250I	21	3	65	180	-40	85	-10	-	-	-
GT-250IB UV	21	3	65	180	-40	85	-10	Y	-	-
GT-250ST	21	3	65	220	-40	85	-10	-	-	-
GT-250STB UV	21	3	65	220	-40	85	-10	Y	-	-
GT-280ST	21	3	70	220	-40	85	-10	-	-	-
GT-280STB UV	21	3	70	220	-40	85	-10	Y	-	-
GT-300HD	21	6	82	530	-40	85	-10	-	-	-
GT-300HDB UV	21	6	82	530	-40	85	-10	Y	-	-
GT-300I	21	3	76	180	-40	85	-10	-	-	-
GT-300IB UV	21	3	76	180	-40	85	-10	Y	-	-
GT-300ST	21	3	82	220	-40	85	-10	-	-	-
GT-300STB UV	21	3	82	220	-40	85	-10	Y	-	-
GT-350ST	21	3	90	220	-40	85	-10	-	-	-
GT-350STB UV	21	3	90	220	-40	85	-10	Y	-	-
GT-370HD	21	6	102	530	-40	85	-10	-	-	-
GT-370HDB UV	21	6	102	530	-40	85	-10	Y	-	-
GT-370I	21	3	102	180	-40	85	-10	-	-	-

GT-370IB UV	21	3	102	180	-40	85	-10	Y	-	-
GT-370ST	21	3	102	220	-40	85	-10	-	-	-
GT-370STB UV	21	3	102	220	-40	85	-10	Y	-	-
GT-400HD	21	6	102	530	-40	85	-10	-	-	-
GT-400HDB UV	21	6	102	530	-40	85	-10	Y	-	-
GT-400ST	21	3	105	220	-40	85	-10	-	-	-
GT-400STB UV	21	3	105	220	-40	85	-10	Y	-	-
GT-430ST	21	3	112	220	-40	85	-10	-	-	-
GT-430STB UV	21	3	112	220	-40	85	-10	Y	-	-
GT-450HD	21	6	118	530	-40	85	-10	-	-	-
GT-450HD UV	21	6	118	530	-40	85	-10	Y	-	-
GT-450HDL	21	8	118	800	-40	85	-10	-	-	-
GT-450HDL UV	21	8	118	800	-40	85	-10	Y	-	-
GT-500HD	21	6	140	530	-40	85	-10	-	-	-
GT-500HD UV	21	6	140	530	-40	85	-10	Y	-	-
GT-500ST	21	3	140	220	-40	85	-10	-	-	-
GT-500STB UV	21	3	140	220	-40	85	-10	Y	-	-
GT-550HD	21	6	160	530	-40	85	-10	-	-	-
GT-550HDB UV	21	6	160	530	-40	85	-10	Y	-	-
GT-550HDL	21	10	160	800	-40	85	-10	-	-	-
GT-550HDLB UV	21	10	160	800	-40	85	-10	Y	-	-
GT-600HDL	21	10	175	800	-40	85	-10	-	-	-
GT-600HDLB UV	21	10	175	800	-40	85	-10	Y	-	-
GT-650HDL	21	10	190	800	-40	85	-10	-	-	-
GT-650HDLB UV	21	10	190	800	-40	85	-10	Y	-	-
GT-700HDL	21	10	200	800	-40	85	-10	-	-	-
GT-700HDLB UV	21	10	200	800	-40	85	-10	Y	-	-

GT-760HDL	21	10	225	800	-40	85	-10	-	-	-
GT-760HDLB UV	21	10	225	800	-40	85	-10	Y	-	-
GT-80M	21	3	16	80	-40	85	-10	-	-	-
GT-80MB UV	21	3	16	80	-40	85	-10	Y	-	-
GT-810HDL	21	10	240	800	-40	85	-10	-	-	-
GT-810HDLB UV	21	10	240	800	-40	85	-10	Y	-	-
GT-920HDL	21	10	265	800	-40	85	-10	-	-	-
GT-920HDL UV	21	10	265	800	-40	85	-10	Y	-	-



The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2022 UL LLC."